

APPLICATION

Internal blinds



Roller Blinds



Roof light Blinds



Roman Shades



Decorative Panels



Velums



Skylight Blinds

Tensile structures



Frame-Mounted



Stretched Ceilings



Fixed or Mobile Partitions, Walls and Separations



Shaped Structures



Volume Structures

Flooring & Wallcovering



Wallcovering Partitions




Rolls Flooring



Tiles Flooring

2000 N



2000 N

THE MAIN THERMAL AND OPTICAL FACTORS

THERMAL FACTORS

**Ts Solar transmittance**  
proportion of solar energy transmitted through the fabric. A low percentage means the fabric performs well at reducing solar energy.

**Rs Solar reflectance**  
proportion of solar radiation reflected by the fabric. A high percentage means the fabric performs well at reflecting solar energy.

**As Solar absorptance**  
proportion of solar radiation absorbed by the fabric. A lowpercentage means the fabric absorbs little solar energy. Solar radiation is always partially transmitted through, absorbed or reflected by the fabric. The sum of all 3 equals 100.  
**Ts + Rs + As = 100% of solar energy.**

**g<sub>tot</sub> Total solar factor**  
solar energy which actually penetrates into a room through the blind and glazing. A low value means good thermal performance.

OPTICAL FACTORS

**OF Openness Factor**  
relative area of the openings in the fabric (hole). It is considered as independent of the colour. For fabrics with the same weave, it should be measured using the darkest colour in the range.

**Tv Visible light transmittance**  
total percentage of light radiated through the fabric over a wavelength of 380 to 780nm (nanometers), called the visible spectrum (total illumination).

Thermal and optical factors

Description Colours	OF 3%							
	Thermal factors						Optical factors	
	Fabric			Fabric + glazing g - value			Tv	Tuv
	Ts	Rs	As	1/8" CL	1/4" C/L	1/4" HA		
N001 White I White	22	67	11	0.36	0.35	0.28	17	5
N002 White I Beige	21	57	22	0.41	0.40	0.29	16	3
N003 White I Grey	14	47	39	0.45	0.43	0.32	10	4
N701 Charcoal I Charcoal	4	7	89	0.62	0.60	0.41	3	3
N702 Charcoal I Sable	3	21	76	0.55	0.52	0.38	2	2
N703 Charcoal I Dim Grey	3	12	85	0.59	0.56	0.39	2	2
N801 Bronze I Bronze	7	12	81	0.59	0.57	0.40	4	3

2000 N  
2015-2017

OPENNESS FACTOR 3%



2000 N

FABRIC			SUNSHADOW		
Technical specifications	Average Values	Standard			
Openess Factor	3%	Microscopic Method			
Composition	Green PVC 75% Polyester 25%	ISO 1833-1:2006			
Environment		• Oeko-tex standard 100 • GREENGUARD Children & Schools			
Thickness	0.39mm (±5%)	ISO 5084-1996			
Weight	310g / m² (±5%)	ISO 3081-1977			
Fabric Count (sq.inch)	76ends X 64picks (±5%)	ISO 7211/2-1984			
Tensile Strength (daN/5cm)	Warp 113, Weft 95 (±5%)	ISO 1421-1998			
Tearing Strength (daN)	Warp 2.6, Weft 2.1 (±5%)	ISO 4674-1977			
Colourfastness	7 - 8 Grade ISO Blue Scale	ISO 105 B02:1994			
Fire resistance	M1	NF P 92-512 (EU)			
	FR	NFPA 701 (USA)			
	Type B	BS 5867 (U.K)			
	B1, B2	DIN 4102 (GERMANY)			
	AS/NZS	ISO 1530.3-1999 (AUSTRALIA)			
	B1	GB / 51455-1997(CHINA)			
	KFI	ISO 5659 (KOREA)			
Standard Width	2.0M / 2.5M / 3.0M				
Cutting	best result with crush cutting				
Welding	thermal, HF, ultrasonic, sewing				
Cleaning	remove dust from the fabric surface, then wipe gently with a humid soft sponge while using a mild detergent				



BREATHEEASY

Using a very clever scientific process, Alkenz has removed odor causing components from their specially formulated non-toxic PVC compound. We call it Low Odor Emission Technology(LOE). As a result, the entire Sunshadow® Sunscreen range has earned GREENGUARD® endorsement for Indoor Air Quality. Unlike most other Blind Fabrics, Sunshadow® Sunscreen has minimal odor and therefore is has not been linked to complaints from consumers who develop headaches or feel unwell after inhaling strong odors from other Blind Fabrics. LOE Technology is ideal for residential environments, but particularly beneficial for commercial developments where odors from Blind Fabrics can linger and circulate through air-conditioning making it uncomfortable for office workers.



FUTUREFOCUSED

By reputation, Alkenz is an innovative chemical company and by their own admission, this company has a strong environmental compass. A commitment already demonstrated when Alkenz developed the world's first non-toxic PVC compound which is safe for families and workers. By investing heavily in research and development, Alkenz will continue to create newer, better and safer methods for manufacturing products. Alkenz will deliver products that meet the needs of consumers' now, while ensuring quality, durability and contemporary styling. Through the ongoing development of Sunshadow® Sunscreen Blind Fabric, Alkenz is committed to achieving - The World's BEST Sun Protection for Windows.



QUALITY

Alkenz is a company with a strong social conscience and it is from this platform that outstanding quality processes have been developed. Every aspect of Alkenz manufacturing from top to bottom is quality managed in a state-of-the-art facility that encompasses a formulation plant, laboratory research and development and a weaving factory. As you would expect, Alkenz has achieved ISO-9001 Quality Standards certification. Alkenz has applied the full extent of its quality procedures and resources to the development and manufacture of Sunshadow® Sunscreen blind fabrics. To this end, Sunshadow® Sunscreen has been endorsed by the world's most respected independent testing organizations: Oeko-Tex® which tests for the presence of volatile organic compounds; GREENGAURD® which tests for indoor air quality; and Ecospecifier® which is committed to ecologically aware, 'green' building products. Further, Sunshadow® Sunscreen has outstanding Fire Retardant qualities which have achieved international flame and smoke regulation accreditation. Sunshadow® Sunscreen has also achieved anti-bacterial and anti-fungal certification. The Sunshadow® Sunscreen range of fashion colors is also sound, supported by comprehensive colorfastness testing. Using Blue Scale exposure to "Very Intense" light, testing has delivered a grading of 7 to 8 from a possible best score of 8. As the world becomes more aware of greenhouse gases, carbon footprints and the depletion of natural resources, consumers are making conscious decisions to reduce energy consumption. Sunshadow® Sunscreen by Alkenz achieves between 20% to 40% in energy savings due to reduced interior temperature in summer and less heat loss in winter, and all without sacrificing the view! Sunshadow® Sunscreen offers see-through qualities and natural light while maintaining day time privacy.




ENVIRONMENTALLY AWARE

With origins in chemical technology, Alkenz is aware more than most of the need for environmental responsibility. We are among the world's leading manufacturers to embrace the environment and human well-being by developing and implementing better and safer products. This commitment is evident in the world's first non-toxic PVC compound which has been developed by Alkenz to coat polyester to form a yarn that is stronger, lighter and less expensive to produce than traditional vinyl coated glass fiber fabrics. But perhaps of greatest importance, Sunshadow® Sunscreen has been officially declared safe when independently tested for Volatile Organic Compounds by Oeko-Tex® Standards 100. In the process of creating safe non-toxic PVC, Alkenz removed the odors that can reduce interior air quality when Blind Fabrics are installed in homes and workplaces, unlike most competitor's Sunscreen products that pollute interior spaces with strong odors. We call this process of LOE - Low Odor Emission Technology and it has earned GREENGUARD® Indoor Air Quality endorsement. Further, Sunshadow® Sunscreen has been endorsed by Ecospecifier®, an international organization dedicated to sustainable building products and ecologically aware building practices. Ecospecifier® has tested and concluded that Sunshadow® Sunscreen Blind Fabrics are 'green'.



2000 N



3%

2000 N

COLOR&RANGE



N001  
White | White



N002  
White | Beige




N003  
White | Grey




N702  
Charcoal | Sable



N703  
Charcoal | Dim Grey



N801  
Bronze | Bronze



N701  
Charcoal | Charcoal

Alkenz

2000 N